Technical datasheet

CROSS POWER 2T

Fully synthetic high-performance engine oil for 2-stroke Off-Road motorcycles

Description

Fully synthetic high-performance engine oil for 2-stroke Off-Road motorcycles. When this oil was developed – in direct cooperation with racing teams and motorcycle manufacturers – special attention was paid to the specific demands of Off-Road use.

Product features

- fully synthetic
- especially formulated for Off-Road use
- racing quality
- reduces combustion residues
- low-smoke formula
- for pre-mix and separate lubrication



Field of application

MOTOREX CROSS POWER 2T has been especially developed for Off-Road use. It can be used for pre-mix and separate lubrication (mixing ratios in accordance with manufacturer's recommendation).

Notes

Always follow the manufacturer's specifications.

Specifications

API TC, ISO-L-EGD, JASO FD

Technical Data

Properties	Test according to	Unit	Values
Colour			red
Density at 20 °C		g/cm3	0.874
Viscosity at 40°C	DIN 51562-1	mm2/s	56.0
Viscosity at 100°C	DIN 51562-1	mm2/s	9.6
Viscosity index	DIN ISO 2909		156.0
Flash point PMCC	ASTM 93	°C	>= 90
Pourpoint	ASTM D5950	°C	-54
Sulphate residue content	DIN EN ISO 6245	%	0.20
TBN	DIN ISO 3771	mg KOH/g	2.20
Phosphor		%	0.000

The above information corresponds to the current state of our knowledge. We reserve the right to make changes. The performance characteristics indicated are based on testing and production tolerances standard in this industry. A safety data sheet is available.

MOTOREX USA Inc.
993 Federal Road
Brookfield, CT06804-1108,United States
Tel. +1 203-775-1291
motorex.com

MOTOREX AG
Bern-Zürich-Strasse 31
4901 Langenthal, Schweiz
Tel. +41 62 919 75 75
motorex.com

26.11.2024 / 07