MOTUL FORK OIL FACTORY LINE VERY LIGHT 2.5W

High Performance Hydraulic Fluid for any telescopic fork
100% Synthetic
VERY LIGHT

TYPE OF USE

Hydraulic fluid for racing applications.

Specially formulated for SHOWA, KAYABA, OHLINS, WP forks, and any type of upside/down or conventional telescopic fork.

PERFORMANCES

Reduced internal friction, specially fork tubes and seals thanks to the exclusive anti-friction additive designed and developed by MOTUL.

Outstanding suspension performance as soon as riding and maintained performance in time.

High performance anti-foam avoiding air transfer to the air chamber to maintain suspension performance.

Anti-wear and extreme pressure properties. Anti-corrosion. Seals protection.

RECOMMENDATIONS

MOTUL Fork Oil Factory Line can be mixed to obtain the required absorption effect.

Use the exact quantity recommended by the fork manufacturer.

PROPERTIES

Viscosity grade		2.5W
Density at 20°C (68°F)		0.834
Viscosity at 40°C (104°F)	ASTM D445	15.0 mm²/s
Viscosity at 100°C (212°F)	ASTM D445	3.5 mm²/s
Viscosity Index	ASTM D2270	112.0
Pour point	ASTM D97	-39.0 °C / -38.0 °F
Flash point	ASTM D92	205.0 °C / 401.0 °F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 49 Kyalami Blvd, Kyalami Business Park - 1684 - Midrand - +27820454357 - www.motul.com

MOTUL FORK OIL FACTORY LINE VERY LIGHT 2.5W

High Performance Hydraulic Fluid for any telescopic fork
100% Synthetic
VERY LIGHT

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.
Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 49 Kyalami Blvd, Kyalami Business Park - 1684 - Midrand - +27820454357 - www.motul.com