Product information
Copper Spray

PI 25/09/30/2026



Description
Copper-colored release agent and lubricant in aerosol form for machine elements which are subjected to high thermal stress. Especially suitable for problem-free dismantling after long periods of operation.

Properties
- universal application
- eliminates squeaks
- resistant to acceleration forces
- resistant to hot water, salt water and splash water
- prevents transmission of vibration
- long-term corrosion protection
- lubricant and release effect
- protects from welding and seizing
- outstanding thermal stability
- high bond strength

Technical data

Color / appearance	nicht bestimmt
Base	Mineralöl. Polymergemisch, Metallpigmente
Metal pigment	copper
Propellant	DME (Dimethylether)
Operating temperature range	-30 to +1100 °C
Form	liquid, aerosol
Odor	characterisitc

Areas of application
Noise damping and repairs in the entire brake range* (e.g. disk brakes and drum brakes), corrosion protection and lubrication of components (e.g. hinges, joints, screws, etc.), lubrication and separation protection before fusion, seizing of components under high thermal load (e.g. exhaust pipe, heat exchanger, boiler, turbines, fittings, etc.).

*Please follow the manufacturer's advice with regard to products which contain copper.

Application
Brakes
Clean components which are to be treated such as the back of brake shoes, mounting surfaces and fasteners. Apply an appropriate amount of Copper Spray.

Repairs and preventive maintenance
Clean the parts to be treated. Apply an appropriate amount of Copper Spray according to the maintenance instructions.

Handling the aerosol can
Shake can vigorously until the balls have worked free. After use, clear spray nozzle (hold can with spray head upside down) by spraying until only pure propellant emerges.

Available pack sizes

250 ml Can aerosol	1520 DE-EN-IT
250 ml Can aerosol	1824 AR-DE-EL-FR-NL
250 ml Can aerosol	2864 DA-EN-FI-NO-SV
250 ml Can aerosol	3970 DE-PL-RU

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com