Product information

PI 32/11/05/2026

Motorsystemreiniger Benzin



Description

Combines modern additive technology with a high proportion of cleaning and corrosion-protecting additives. Also removes extremely heavy deposits such as those found in direct injection systems. Reduces the risk of engine damage and protects the entire fuel system against corrosion. Restores engines to original performance levels.

Properties

- tested for the use with catalytic converters
- removes deposits from entire fuel system
- prevents corrosion in the fuel system
- assures an optimum mixture
- keeps injection nozzles clean

Technical data

Shelf life in original sealed container	60 months
Color / appearance	yellow, clear
Odor	aromatic odor
Density at 15 °C	0,816 g/ml
Flash point	>63 °C

Areas of application

For all gasoline injection systems with and without turbocharging, particularly with direct injection. To be added directly into the fuel tank. Sufficient for up to 75 l of fuel.

Available pack sizes

300 ml Can sheet metal	1712 IT
300 ml Can sheet metal	5129 DE-NL
300 ml Can sheet metal	21492 DE-EN
300 ml Can sheet metal	21624 CS-RO-SK

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com