# Product information
## Motorbike Radiator Cleaner

PI 50/08/18/2026




### Description
Concentrate for cleaning cooling circuits. Deposits in the cooling/heating system create blockages for heat exchange and they also block thermostat valves and control mechanisms. When engine temperatures are too high, the engine runs uneconomically and suffers excessive wear at considerable risk of damage. Removes deposits containing oil and lime and ensures that the engine runs reliably and at the optimum temperature. Does not contain aggressive acids or alkalis.

### Properties
- disperses sludge
- chemical conversion of lime
- compatible with antifreeze
- neutralizes acids
- removes oil and grease-based contaminants
- neutral behavior on rubber and plastics

### Technical data

| | |
|---|---|
| Form | liquid |
| Color / appearance | colourless, unclear |
| Hazard class as per German VbF | none |
| pH value | 10,31 |
| Solubility in water | soluble |
| Odor | characteristic |
| Density at 20 °C | 1,014 g/cm³ |

### Areas of application
Suitable for all cooling water circuits. Compatible with all conventional coolant additives and antifreezes.

### Comment
Store free of frost.

The treated product contains biocides as protective agents. Contains a mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1).

### Application
LIQUI MOLY recommends adding Motorbike Radiator Cleaner if problems arise or before changing the coolant. Depending on the level of contamination, run the engine at operating temperature for 10-30 minutes. Drain the cleaner and flush out the cooling system with water. Fill cooling system according to manufacturer's specifications. Contents of can are sufficient to treat 5 liters of coolant.

### Available pack sizes

| | |
|---|---|
| 150 ml Can sheet metal | 3042<br>DE-EN-ES |

**Our information is based on thorough research and may be considered reliable, although not legally binding.**

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com